



LUBRI-LAB
INC

TECHNICAL DATA

ALIMEX-1™

H1 food equipment grease

DESCRIPTION

Alimex-1 is distinguished by its exceptional mechanical stability, high dropping point and perform under water washout. It is a state of the art, high performance grease which has been developed by complexing modified, overbased, calcium sulfonates. This technology in many ways outperforms other premium, high temperature greases such as Lithium Complex, Aluminum Complex and Polyurea.

APPLICATIONS

Alimex-1 is a certified H-1 grease for incidental contact with food. It is designed for use in all food processing areas including mixing, baking, cooking, frying, stirring, packaging, cleansing, bottling and canning. **Public works:** Fire hydrant bearing.

FEATURES AND BENEFITS

- Thermal and Mechanical Stability, particularly in the presence of heat and water
- High dropping point, 318°C (608°F) ASTM D2265
- Resists heavy load, Timken OK load, ASTM D2509= 36 kg (80 lbs)
- Excellent EP and Anti-wear properties
- Resistance to Water washout, ASTM D1264, at 80°C (175°F) % loss=0.5
- Resists to many acid and alkaline solutions
- Does not dry
- Resists oxidation: Formulated with white oil. Grease life performance is typically increased by 2 to 3 times that of a regular mineral oil based grease
- Corrosion Resistance: Sulfonates are known and used for their excellent rust prevention properties

The above information is true and precise to the best of our knowledge. All recommendations or suggestions are made without warranty since the circumstances and conditions are beyond our control.

For further information contact: **Lubri-Lab Inc.:** info@lubrilab.com

1540, de Coulomb, Boucherville QC Canada J4B 8A3

Tel.: (888) 449-1626 (450) 449-1626 Fax: (450) 449-9174

www.lubrilab.com

PerformACE 2001 Award Recipient



LUBRI-LAB
INC

TECHNICAL DATA

ALIMEX-1™

H1 food equipment grease

TYPICAL PERFORMANCE

Typical Results

N.L.G.I. GRADE	2
COLOUR	cream
CONSISTENCY, ASTM D 217, 60 strokes, mm/10	280
DROPPING POINT, ASTM D 2265,(608°F) °C.	318
LOW TEMPERATURE TORQUE, ASTM D 1478, @ -18°C (0°F)	
Start	1404
60 minutes	247
LOW TEMPERATURE MOBILITY @ 150 psi, -18°C g/min US Steel Method	19.3

RESISTANCE TO WATER

WATER WASHOUT, ASTM D 1264,at 80°C (175°F) , % lost.	0.5
--	-----

RESISTANCE TO CORROSION

RUST TEST, rating, ASTM D 1743.	pass
SALT FOG CORROSION, ASTM B117, 1 mil d.f.t., hours	>300
COPPER CORROSION, rating ASTM D4048	1B

LEAKAGE & SEPARATION CHARACTERISTICS

OIL SEPARATION, ASTM D 1742, % loss	0.1
-------------------------------------	-----

The above information is true and precise to the best of our knowledge. All recommendations or suggestions are made without warranty since the circumstances and conditions are beyond our control.

For further information contact: **Lubri-Lab Inc.:** info@lubrilab.com
1540, de Coulomb, Boucherville QC Canada J4B 8A3
Tel.: (888) 449-1626 (450) 449-1626 Fax: (450) 449-9174
www.lubrilab.com

PerformACE 2001 Award Recipient



LUBRI-LAB
INC

TECHNICAL DATA

ALIMEX-1™

H1 food equipment grease

RESISTANCE TO OXIDATION

BOMB OXIDATION, ASTM D 942, psi drop after 1000 hours. 6.0

EXTREME PRESSURE & WEAR PERFORMANCE

TIMKEN OK LOAD, ASTM D 2509, (80 Lbs) kg 36
4 BALL EP., ASTM D 2596, Load Wear Index, (136 Lbs) kg 62
Weld Point, (1100 Lbs) kg 500
4 BALL WEAR, ASTM D 2266, mm. 0.45

MECHANICAL STABILITY

MECHANICAL STABILITY, 10,000 strokes, %change ASTM-D217 -1.0
ROLL STABILITY, 50% water, % change in pen ASTM D1831 2.1
WHEEL BEARING LEAKAGE, ASTM D 4290, grams. 1.0
BEARING LIFE, ASTM D 3527, hours 180

Special features: Approved by Agriculture and Agri-Food Canada, Food Production and Inspection Branch for food equipment. For incidental contact with food.

File number: 3100-3/L125

Alimex-1 is a certified H1 grease for incidental contact with food.

File number: NSF: 128001

Availability: Case 50 tubes, 17 kg pail, 55 kg keg, 180 kg drum.

The above information is true and precise to the best of our knowledge. All recommendations or suggestions are made without warranty since the circumstances and conditions are beyond our control.

For further information contact: **Lubri-Lab Inc.:** info@lubrilab.com

1540, de Coulomb, Boucherville QC Canada J4B 8A3

Tel.: (888) 449-1626 (450) 449-1626 Fax: (450) 449-9174

www.lubrilab.com

PerformACE 2001 Award Recipient